

Output Ratings

Generating Set Model	P1000P1	P1100E1
380 – 415V, 50 Hz	1000 kVA 800 kW	1100 kVA 880 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model P1000P1

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P1100E1

These ratings are applicable for supplying continuous electrical power (at variable load) in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO8528-3).

Technical Data

Engine Model:	Perkins 4008TAG2A
Alternator Model:	LL8124B
Number of Cylinders:	8 in line
Cubic Capacity: Litres (cu.in)	30.6 (1864.9)
Bore/Stroke: mm (in)	160 (6.3)/190 (7.5)
Compression ratio:	13.6:1
Aspiration:	Turbocharged, AA Charge Cooled
Frequency:	50 Hz
Engine Speed:	1500 RPM
Gross Engine Power: kW (hp)	969 (1299)
BMEP: kPA (psi)	2537 (367.9)
Piston Speed: m/sec (ft/sec)	9.5 (31.2)
Fuel Consump, P1000P1: 1/hr (USg/hr)	215.4 (56.9)
Fuel Consump, P1100E1: 1/hr (USg/hr)	241.5 (63.8)
Heat Rejection to Exhaust System: kW (Btu/min)	807 (45893)
Heat Rejection to Cooling System: kW (Btu/min)	349 (19847)
Total Radiated Heat: kW (Btu/min)	151 (8587)
Exhaust Temperature: °C (°F)	465 (869)
Radiator Cooling Air Flow: m3/min (cfm)	1152 (40683)
Combustion Air Flow: m3/min (cfm)	80.5 (2843)
Exhaust Gas Flow: m3/min (cfm)	200 (7063)

Note: Standard reference conditions 27°C (80°F) Air Inlet Temp, 152.4m (500ft)A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

Dimensions and Weights

Length: mm(in)	Width: mm(in)	Height: mm(in)	Dry: kg (lb)	Wet: kg (lb)
4790 (188.6)	2036 (80.2)	2235 (88.0)	7334 (16169)	7568 (16685)
Dry = With Lube Oil		Wet = With Lube Oil and Coolant		

Generating set pictured may include optional accessories

TEL./ FAX. : 0044 2893 355674

Website:www.marapco.com

N. Ireland - UK

Made in UK

In line with our policy of continuous product development, we reserve the right to change specification without notice.

Marapco
GENERATORS



YOUR PARTNER IN POWER

P1000P1 - P1100E1



Jan-08