

Output Ratings

Generating Set Model	P1250P3	P1375E3
380 – 415V, 50 Hz	1250 kVA 1000 kW	1375 kVA 1100 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model P1250P3

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P1375E3

These ratings are applicable for supplying continuous electrical power (at variable load) in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO8528-3).

Technical Data

Engine Model:	Perkins 4012-46TWG2A
Alternator Model:	LL8224L
Number of Cylinders:	12 Vee
Cubic Capacity: Litres (cu.in)	45.8 (2797.5)
Bore/Stroke: mm (in)	160.0 (6.30)/190.0 (7.5)
Compression ratio:	13.1:1
Aspiration:	Turbocharged, AA Charge Cooled
Frequency:	50 Hz
Engine Speed:	1500 RPM
Gross Engine Power: kW (hp)	1217.0 (1632)
BMEP: kPA (psi)	2124.0 (308)
Piston Speed: m/sec (ft/sec)	9.5 (31.2)
Fuel Consump, P1250P3: 1/hr (USg/hr)	257.1 (67.9)
Fuel Consump, P1375E3: 1/hr (USg/hr)	283.8 (75)
Heat Rejection to Exhaust System: kW (Btu/min)	1001.0 (56926)
Heat Rejection to Cooling System: kW (Btu/min)	401.0 (22804)
Total Radiated Heat: kW (Btu/min)	89.0 (5061)
Exhaust Temperature: °C (°F)	422 (792)
Radiator Cooling Air Flow: m3/min (cfm)	1116.0 (39411)
Combustion Air Flow: m3/min (cfm)	109.0 (3849)
Exhaust Gas Flow: m3/min (cfm)	180.0 (6357)

Note: Standard reference conditions 27°C (80°F) Air Inlet Temp, 152.4m (500ft)A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

Dimensions and Weights

Length: mm(in)	Width: mm(in)	Height: mm(in)	Dry: kg (lb)	Wet: kg (lb)
4820 (189.8)	1895 (74.6)	2424 (95.4)	9059 (19972)	9255 (20404)
Dry = With Lube Oil		Wet = With Lube Oil and Coolant		

Generating set pictured may include optional accessories

TEL./ FAX. : 0044 2893 355674

Website: www.marapco.com

N. Ireland - UK

Made in UK

In line with our policy of continuous product development, we reserve the right to change specification without notice.

Marapco

GENERATORS



YOUR PARTNER IN POWER

P1250P3 - P1375E3



Jan-08