

Output Ratings

Generating Set Model	P1825	P2000E
380 - 415V, 50Hz	1825.1 kVA 1460.1 kW	2000.0 kVA 1600.0 kW

Ratings at 0.8 pf

Ratings Definitions:

Prime Power – Model P1825

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P2000E

These ratings are applicable for supplying continuous electrical power (at variable load) in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO8528-3).

Technical Data

Engine Make & Model:	Perkins 4016TAG1A
Alternator Model:	LL9124H
No. of Cylinders/Alignment:	16 / Vee
Displacement: litres (cu.in)	61.1 (3730.0)
Bore/Stroke: mm (in)	160.0 (6.3)/190.0 (7.5)
Compression ratio:	13.6:1
Induction:	Turbocharged Air To Air Charge Cooled
Frequency:	50 Hz
Engine Speed:	1500 RPM
Gross Engine Power: kW (hp)	1741.0 (2335.0)
BMEP: kPA (psi)	2279.0 (330.5)
Piston Speed: m/sec (ft/sec)	9.5 (31.2)
Fuel Consump, P1825: 1/hr (USg/hr)	378.3 (99.9)
Fuel Consump, P2000E: 1/hr (USg/hr)	419.6 (110.8)
Heat Rejected to Exhaust System: kW (Btu/min)	1276.0 (72565)
Heat Rejected to Water & Lube Oil: kW (Btu/min)	629.0 (35771)
Heat Radiation to Room: kW (Btu/min)	177.0 (10066)
Exhaust Gas Temperature: °C (°F)	439 (822)
Radiator Cooling Air Flow: m3/min (cfm)	2058.0 (72678)
Combustion Air Flow: m3/min (cfm)	140.0 (4944)
Exhaust Gas Flow: m3/min (cfm)	343.0 (12113)

Note: Standard reference conditions 27°C (80°F) Air Inlet Temp, 152.4m (500ft) A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

Dimensions and Weights

Length: mm(in)	Width: mm(in)	Height: mm(in)	Dry: kg (lb)	Wet: kg (lb)
5725 (225.4)	2300 (90.6)	3020 (118.9)	15500 (34172)	15700 (34613)
Dry = With Lube Oil		Wet = With Lube Oil and Coolant		

Generating set pictured may include optional accessories

TEL./ FAX. : 0044 2893 355674

Website: www.marapco.com

N. Ireland - UK

Made in UK

In line with our policy of continuous product development, we reserve the right to change specification without notice.



YOUR PARTNER IN POWER

P1825 / P2000E



Jan-08