

Output Ratings		
Generating Set Model	P230H2	P250HE2
380 – 415V, 50 Hz	230.0 kVA	250.0 kVA
	184.0 kW	200.0 kW
480V, 60 Hz	240.0 kVA	265.0 kVA
	192.0 kW	212.0 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model P230H2

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P250HE2

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator model is peak continuous rated (as defined in ISO 8528-3).

Technical Data

Engine Make & Model:	Perkins 1306C-E87TAG4	
Alternator Model:	LL5014H	
No. of Cylinders/Alignment:	6 / In Line	
Displacement: Litres (cu.in)	8.7 (530.9)	
Bore/Stroke: mm (in)	116.6 (4.6)/135.9 (5.4)	
Compression ratio:	16.9:1	
Induction:	Turbocharged Air To Air Charge Cooled	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	228.5 (306.0)	246.8 (331.0)
BMEP: kPA (psi)	2099.0 (304.5)	1890.0 (274.1)
Piston Speed: m/sec (ft/sec)	6.8 (22.3)	8.2 (26.9)
Fuel Tank Capacity: Litres (US Gal)	350 (92.5)	350 (92.5)
Fuel Consump, P230H2: 1/hr (USg/hr)	56.3 (14.9)	60.1 (15.9)
Fuel Consump, P250HE2: 1/hr (USg/hr)	61.2 (16.2)	64 (16.9)
Heat Rejection to Exhaust System: kW (Btu/min)	117 (6654)	125 (7109)
Heat Rejection to Water & Lube Oil: kW (Btu/min)	96 (5459)	105 (5971)
Heat Radiated to Room: kW (Btu/min)	37 (2104)	40 (2275)
Exhaust Temperature: °C (°F)	508 (946)	447 (836)
Radiator Cooling Air Flow: m ³ /min (cfm)	424.2 (14980)	560.4 (19790)
Combustion Air Flow: m ³ /min (cfm)	14.9 (526)	20.2 (713)
Exhaust Gas Flow: m ³ /min (cfm)	44.5 (1572)	58.1 (2052)

Note: Standard reference conditions 27°C (80°F) Air Inlet Temp, 152.4m (500ft)A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, ClassA2.

Dimensions and Weights

Length: mm(in)	Width: mm(in)	Height: mm(in)	Dry: kg (lb)	Wet: kg (lb)
2960 (116.5)	1003 (39.5)	1718 (67.6)	2100 (4630)	2137 (4711)
Dry = With Lube Oil		Wet = With Lube Oil and Coolant		

Generating set pictured may include optional accessories



YOUR PARTNER IN POWER

P230H2 / P250HE2

TEL./ FAX. : 0044 2893 355674

Website: www.marapco.com

N. Ireland - UK

Made in UK

In line with our policy of continuous product development, we reserve the right to change specification without notice.



Jan-08