

Output Ratings

Generating Set Model	P800P1	P900E1
380 – 415V, 50 Hz	800 kVA 640 kW	900 kVA 720 kW
480V, 60 Hz	835.0 kVA 668.0 kW	938.0 kVA 750.4 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model P800P1

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P900E1

These ratings are applicable for supplying continuous electrical power (at variable load) in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated. (as defined in ISO8528-3).

Technical Data

Engine Model:	Perkins 4006TAG3A	
Alternator Model:	LL7024P	
Number of Cylinders:	6 in line	
Cubic Capacity: Litres (cu.in)	22.9 (1398.7)	
Bore/Stroke: mm (in)	160 (6.3)/190 (7.5)	
Compression ratio:	13.6:1	
Aspiration:	Turbocharged, AA Charge Cooled	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	786 (1054)	839.0 (1125)
BMEP: kPA (psi)	2743 (397.9)	2440.0 (353.9)
Piston Speed: m/sec (ft/sec)	9.5 (31.2)	11.4 (37.4)
Fuel Tank Capacity: Litres (US Gal)	1494 (394.7)	1494 (394.7)
Fuel Consump, P800P1: 1/hr (USg/hr)	163 (43.1)	188.3 (49.7)
Fuel Consump, P900E1: 1/hr (USg/hr)	183.5 (48.5)	211.9 (56)
Heat Rejection to Exhaust System: kW (Btu/min)	515 (29288)	698.0 (39695)
Heat Rejection to Cooling System: kW (Btu/min)	300 (17061)	320.0 (18198)
Total Radiated Heat: kW (Btu/min)	97.1 (5522)	106.0 (6028)
Exhaust Temperature: °C (°F)	500 (932)	500 (932)
Radiator Cooling Air Flow: m ³ /min (cfm)	1134 (40047)	1326 (46827)
Combustion Air Flow: m ³ /min (cfm)	73 (2578)	78.0 (2755)
Exhaust Gas Flow: m ³ /min (cfm)	193 (6816)	209.0 (7381)

Note: Standard reference conditions 27°C (80°F) Air Inlet Temp, 152.4m (500ft) A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

Dimensions and Weights

Length: mm (in)	Width: mm (in)	Height: mm (in)	Dry: kg (lb)	Wet: kg (lb)
4280 (168.5)	1912 (75.3)	2277 (89.6)	6259 (13799)	6370 (14043)

Dry = With Lube Oil Wet = With Lube Oil and Coolant

Generating set pictured may include optional accessories



YOUR PARTNER IN POWER

P800P1 – P900E1

TEL./ FAX. : 0044 2893 355674

Website: www.marapco.com

N. Ireland - UK

Made in UK

In line with our policy of continuous product development, we reserve the right to change specification without notice.



Jan-08